

# NKCR2.E68961 - Auxiliary Devices - Component

## Auxiliary Devices - Component

See General Information for Auxiliary Devices - Component

### IDEC CORP

6-64 NISHIMIYAHARA 2-CHOME  
YODOGAWA-KU, OSAKA 532-0004 JAPAN

E68961

### Investigated to ANSI/UL 508

**AS-interface stop at work slaves, open type** Model(s) XA1E may be preceded by prefix FB1W, followed by BV or LV, followed by 3, 4 or 5, followed by Z, followed by 10 or 11, may be followed by 4 thru 24, followed by C1 or C2, followed by R, RH or N, may be followed by Y, may be followed by 0 or 1, may be followed by 1 or 2.

XW1E may be preceded by prefix FB1W, followed by BV or LV, followed by 3, 4 or 5, followed by Z, followed by 10 or 11, may be followed by 4 thru 24, followed by C1 or C2, followed by R, RH or N, may be followed by Y, may be followed by 0 or 1, may be followed by 1 or 2.

**Auxiliary Device Open type Buzzer** Model(s) HW followed by 1, followed by Z, may be followed by P1 or P2, may be followed by F, followed by 2, followed by P, followed by Q4, followed by R, Y, A, G, W, S, PW or B, may be followed by any letters and/or numbers employing hyphens in various locations.

**Auxiliary Device Open type, Industrial Magnetic card relays** Model(s) RV3T-1G, RV3T-2G, RV3T-3G

**Auxiliary devices** Model(s) HS5E Series

**Combination display lights** Model(s) LD6A may be followed by -0, -1, -2, -3, -4 or -5, followed by D, W, G, P or K, may be followed by Z or C, may be followed by Q or D.\*

SLC30N followed by 01 thru 10, followed by 01 thru 20, followed by -DD, -DF, -DHM, -DS, -DW, -TD, -TE or -TS, followed by 1, 2, 3, 6 or 8, may be followed by -NKCR2.

SLC40N followed by 01 thru 07, followed by 01 thru 15, followed by -DD, -DE, -DEM, -DF, -DHT, -DW, -TD or -TE, followed by 1, 2, 3, 6 or 8, may be followed by -NKCR2.

**Enabling switches, "HE6B Series"** Model(s) HE6B-M2+ +##, HE6B-M2+ +##-TK2546-1, HE6B-M2+ +V##

**Enabling switches** Model(s) HE1B-M1\*, HE2B-M2\*, HE2B-M6\*

HE2G followed by 2, followed by 0, 1, 1S, 2, 2S, 11S, 21S, 12S or 22S, followed by H or C, may be followed by letters and/or numbers, followed by blank, B, N, 1Y, 1B or 1N.\*

HE2G-X followed by 2, followed by 0, 1, 1S, 2, 2S, 11S, 21S, 12S or 22S, followed by H or C, may be followed by letters and/or numbers, followed by blank, B, N, 1Y, 1B or 1N.\*

HE3B-M2\*, HE5B-M2\*

**Grip switch enclosures** Model(s) HE9Z

**LED illuminated display lights** Model(s) SLC30-0101\*, SLC30-0102\*, SLC30-0103\*, SLC30-0202\*, SLC40-0101\*, SLC40-0102\*, SLC40-0103\*, SLC40-0202\*, SLD24\*

**LED illuminated miniature pilot lights, "AP Series"** Model(s) AP1M, AP2M, AP6M, AP8M

**Magnetically operated switches, for use in electronic data processing equipment or office appliance and business equipment (nonindustrial)** Model(s) RV3S may be followed by B, G, 3B or 3G, followed by 05S thru 24S.

**Push button switches, "AB6E Series"** Model(s) AB6E

**Push button switches** Model(s) HA may be followed by 1, may be followed by E, followed by -, may be followed by V, may be followed by 2, followed by S, may be followed by 1 or 2, may be followed by V, may be followed by R, N, Y, B, G, W or S.\*

XA1E followed by BV, LV, or TV, followed by 3, 4, 5, 3T, or 4T, may be followed by G, followed by 0, 1, 2, or 3, followed by 1, 2, 3, or 4, may be followed by Q1, Q2, Q3, or Q4, may be followed by V, followed by R, R-EMO, RH, RH-EMO, RM, N, Y, B, G, W, or S, may be followed by optional letters and/or numbers

XA1E Unibody Type

XW1E followed by BV, LV, or TV, followed by 3, 4, 5, 3T, or 4T, may be followed by G, followed by 0, 1, 2, or 3, followed by 1, 2, 3, or 4, may be followed by Q1, Q2, Q3, or Q4, may be followed by V, followed by R, R-EMO, RH, RH-EMO, RM, N, Y, B, G, W, or S, may be followed by optional letters and/or numbers

XW1E or XA1E followed by BV, LV, or TV, followed by 3, 4, 5, 3T, or 4T, may be followed by G, followed by 0, 1, 2, or 3, followed by 1, 2, 3, or 4, may be followed by Q1, Q2, Q3, or Q4, may be followed by V, followed by R, R-EMO, RH, RH-EMO, RM, N, Y, B, G, W, or S, may be followed by optional letters and/or numbers that may employ hyphens

XW1E-xxxxxxx-BC Series

**Push button switches, unibody Type** Model(s) XA1E

**Push buttons** Model(s) Contact Unit Model XW-C or XA-C may be followed by T, followed by 0, 1, or 2, or 3, followed by 1, 2, 3, or 4, may be followed by Q1, Q2, Q3, or Q4, may be followed by V, may be followed by R, may be followed by optional letters and/or numbers, that may employ hyphens

Model XW-C may be followed by T, followed by 0, 1, or 2, followed by 1, 2, 3, or 4, may be followed by Q4, may be followed by V, may be followed by R, may be followed by optional letters and/or numbers

XN Series, XNxx-xxxxxxxx-BC\*

**Relay sockets** Model(s) RV9Z-S01

**Transformers** Model(s) AP2, AP6, APG

Series RV3T followed by -1G, -2G or -3G, may be followed by 03, 04, 05, 06, 09, 10, 12, 15, 18, 21 or 24.

# - Replaced by one letter or number or blank.

\* - May be followed by any letter(s) and/or number(s).

++ - Where ++ is replaced by 00, 01, 02, 10, 11 or 20.

Marking: Company name or tradename "IDEC" or trademark  ,  ,  ,  ,  ,  ,  ,  , model designation, and the Recognized Component Mark,  .

Last Updated on 2019-02-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"