



No.235DOC-0004

Doc No.	D2B133 D5B052
---------	------------------

EU Declaration of Conformity

Identification of the Product : Circuit Breaker for Equipment

Name and address of Manufacturer
IDEC CORPORATION
2-6-64 Nishimiyahara, Yodogawa-Ku,
Osaka 532-0004 Japan

Name and address of the authorized representative :
APEM SAS
55, Avenue Edouard Herriot BP1, 82303
Caussade Cedex, France

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Object of the declaration : Series Name: NRA Series

Model No.: Details are as per attached sheet

The object of the declaration described above is in conformity with the relevant EU harmonization legislation :

2014/35/EU

Low Voltage Directive

2011/65/EU and (EU)2015/863

Restriction of the use of certain hazardous substances
(RoHS) Directive

Applied Union harmonized legislation and references to the relevant harmonization standards used or references the other technical specifications in relation to which conformity is declared.

EN 60934/A2:2013

EN IEC 63000:2018

Where applicable, the notified body

Additional Information :

Signed for and on behalf of the above named manufacturer :

Place and date of issue :

Japan, 20 April, 2016

Name, function :

Japan, 18 November, 2021 (Revised)

Masaki Tsuru, Executive Officer

Signature :

Quality Assurance Center

Masaki Tsuru

Doc No.	D2B133 D5B052
---------	------------------

20 April, 2016
20 July, 2020 (Revised)
Page 1 of 1

Nomenclature

NRA S - 1 1 00 F S - 3 AA - 1 _
 1 2 3 4 5 6 7 8 9 10 11

1. Basic Model Designation
2. Panel cut-out opening
 - S - Round cut-out, Lever handle type
 - N - Rectangular cut-out, Lever handle type
 - R - Rectangular cut-out, Rocker handle type, Illumination optional
3. Number of Poles
 - 1 - Single Pole
 - 2 - Double Pole
 - 3 - Three Pole
4. Internal Circuit
 - 1 - Series trip
5. Auxiliary Switch (ASW)
 - 00 - Without Auxiliary Contacts.
 - 11 - With Auxiliary Contacts
 - 21 - With Alarm Contacts
6. Protection against inrush current
 - None - Without inertial delay fly wheel
 - F - With inertial delay fly wheel
7. Terminal Style
 - None - Tab terminal
 - S - Screw terminal
8. Indicates Rated Current:
 - 0.3A, 0.5A, 0.75A, 1A, 2A, 3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A
9. Time delay-curve
 - MA, AA or BA for AC models
 - MD or AD for DC models.
10. Indicates Rated Current for Indicator Light (for NRAR Illumination type only)
 - 1 - Neon lamp, AC100 to 110V
 - 2- Neon lamp, AC200 to 220V
 - 3- LED lamp, DC4 to 8V
11. Flush Plate (for NRAS type only)
 - None - Without flush plate
 - /WP - With flush plate