



No.235DOC-0005

Doc No.	D2B134 D5B053
---------	------------------

## EU Declaration of Conformity

**Identification of the Product :** Circuit Breaker for Equipment

**Name and address of Manufacturer**  
IDEC CORPORATION  
2-6-64 Nishimiyahara, Yodogawa-Ku,  
Osaka 532-0004 Japan

**Name and address of the authorized representative :**  
APEM SAS  
55, Avenue Edouard Herriot BP1, 82303  
Caussade Cedex, France

**This declaration of conformity is issued under the sole responsibility of the manufacturer.**

**Object of the declaration :** Series Name: NRBM Series  
Model No.: Details are as per attached sheet

**The object of the declaration described above is in conformity with the relevant EU harmonization legislation :**

2014/35/EU

Low Voltage Directive

2011/65/EU and (EU)2015/863

Restriction of the use of certain hazardous substances  
(RoHS) Directive

**Applied Union harmonized legislation and references to the relevant harmonization standards used or references the other technical specifications in relation to which conformity is declared.**

EN 60934/A2:2013

EN IEC 63000:2018

**Where applicable, the notified body**

**Additional Information :**

**Signed for and on behalf of the above named manufacturer :**

Place and date of issue :

Japan, 20 April, 2016

Japan, 18 November, 2021 (Revised)

Name, function :

Masaki Tsuru, Executive Officer  
Quality Assurance Center

Signature :



No.235DOC-0005

Doc No.	D2B134 D5B053
---------	------------------

20 April, 2016  
20 July, 2020 (Revised)  
Page 1 of 1

### Nomenclature

NRBM   1   1   11   F   -   50A   AA  
          1     2   3   4    5           6     7

1. Basic Model Designation
2. Number of poles
  - 1 - Single pole
  - 2 - Double pole
  - 3 - Three pole
3. Internal circuit
  - 1 - Series trip
4. Auxiliary switch (ASW)
  - 00 - Without ASW
  - 11 - With ASW
  - 21 - With Alarm Contacts
5. Protection against inrush current
  - None - Without inertial delay fly wheel
  - F - With inertial delay fly wheel
6. Indicates Rated Current:
  - 1A, 2A, 3A, 5A, 7.5A, 10A
7. Time delay-curve
  - MA, AA or BA for AC models
  - MD or AD for DC models