

和泉公告

IDEC ANNOUNCEMENT

公告号: A20-014

2019年6月 1/3 页

HG2G-V/HG3G-V/HG4G-V和HG5G-V系列人机界面规格之更改

针对型号

HG2G 人机界面(高性能): 2 种类

- HG2G-V5FT22TF-W
- HG2G-V5FT22TF-B

HG3G 人机界面: 4 种类

- HG3G-VAXT22MF-W
- HG3G-VAXT22MF-B
- HG3G-V8XT22MF-W
- HG3G-V8XT22MF-B

HG4G 人机界面: 1 种类

- HG4G-VCXT22MF-B

HG5G 人机界面: 1 种类

- HG5G-VFXT22MF-B

主要更改

产品标识变更如下: 增加了外观 Type 13 和 QR 码

HG2G 人机界面

现时	更改后
<p>Max. Surrounding Air Temp.: -20°C to +60°C Enclosure Type 1, Type "4X Indoor Use Only", and/or Type 12, Class I Div. 2 Groups A, B, C, D.</p>	<p>Max. Surrounding Air Temp.: -20°C to +60°C Enclosure Type 1, Type 4X "Indoor Use Only", Type 12 and/or <u>Type 13</u>, Class I Div. 2 Groups A, B, C, D.</p>

QR code

Type 13

www.idec.com/china

爱德克电气贸易(上海)有限公司

上海市静安区共和路 209 号企业中心第二座 8 楼 电话 (021) 6135 1515, 传真 (021) 6135 6225

和泉公告


IDEC ANNOUNCEMENT

公告号: A20-014

2019年6月 2/3页

HG3G-VA 人机界面


现时	
MADE IN JAPAN Type: HG3G-VAXT22MF-W S/N: 000000-00000 24V DC, 25W Temperature Code: T4	Max. Surrounding Air Temp.: -20°C to +60°C Class I Div.2 Groups A, B, C, D. Enclosure Type 1, Type "4X Indoor Use Only", and/or Type 12.
 Ind. Cont. Eq. for Haz. Loc. Ind. Cont. Eq. (E102542) IDEC CORPORATION	

更改后	
MADE IN JAPAN Type: HG3G-V8XT22MF-W S/N: 000000-00000 24V DC, 22W Temperature Code: T4	Max. Surrounding Air Temp.: -20°C to +60°C Class I Div.2 Groups A, B, C, D. Enclosure Type 1, Type 4X "Indoor Use Only", Type 12 and/or <u>Type 13</u> .
	
 Ind. Cont. Eq. for Haz. Loc. Ind. Cont. Eq. (E102542) IDEC CORPORATION	

Type 13 QR code

HG3G-V8 人机界面

现时	
MADE IN JAPAN Type: HG3G-VAXT22MF-W S/N: 000000-00000 24V DC, 22W Temperature Code: T4	Max. Surrounding Air Temp.: -20°C to +60°C Class I Div.2 Groups A, B, C, D. Enclosure Type 1, Type "4X Indoor Use Only", and/or Type 12.
 Ind. Cont. Eq. for Haz. Loc. Ind. Cont. Eq. (E102542) IDEC CORPORATION	

更改后	
MADE IN JAPAN Type: HG3G-VAXT22MF-W S/N: 000000-00000 24V DC, 25W Temperature Code: T4	Max. Surrounding Air Temp.: -20°C to +60°C Class I Div.2 Groups A, B, C, D. Enclosure Type 1, Type 4X "Indoor Use Only", Type 12 and/or <u>Type 13</u> .
	
 Ind. Cont. Eq. for Haz. Loc. Ind. Cont. Eq. (E102542) IDEC CORPORATION	

Type 13 QR code

www.idec.com/china

爱德克电气贸易(上海)有限公司

上海市静安区共和路 209 号企业中心第二座 8 楼 电话(021)6135 1515, 传真(021)6135 6225




和泉公告

IDEC ANNOUNCEMENT


公告号: A20-014

2019年6月 3/3页

HG4G 人机界面

现时	
<p>MADE IN JAPAN Type: HG4G-VCXT22MF-B S/N: 000000-00000 24V DC, 25W Temperature Code: T4</p>	<p>Max. Surrounding Air Temp. :-20°C to +60°C Class I Div.2 Groups A, B, C, D. Enclosure Type 1, Type "4X Indoor Use Only", and/or Type 12.</p> <p>Ind. Cont. Eq. for Haz. Loc. Ind. Cont. Eq. (E102542) IDEC CORPORATION</p>
更改后	
<p>MADE IN JAPAN Type: HG4G-VCXT22MF-B S/N: 000000-00000 24V DC, 25W Temperature Code: T4</p>	<p>Max. Surrounding Air Temp. :-20°C to +60°C Class I Div.2 Groups A, B, C, D. Enclosure Type 1, Type 4X "Indoor Use Only", Type 12 and/or <u>Type 13</u>.</p>  <p>Ind. Cont. Eq. for Haz. Loc. Ind. Cont. Eq. (E102542) IDEC CORPORATION</p> <p style="text-align: center;">Type 13 QR code</p>

HG5G 人机界面

现时	更改后
<p>Type: H65G-VFXT22MF-B S/N: 000000-00000 24V DC, 27W, SELV, LIM Max. Surrounding Air Temp. :-20°C to 60°C Temperature Code: T4A MADE IN JAPAN</p> <p>Ind. Cont. Eq. for Haz. Loc. Ind. Cont. Eq. (E102542) IDEC CORPORATION</p> <p>Class I Div.2 Groups A, B, C, D. Enclosure Type 1, Type 4X Indoor Use only, and/or Type 12.</p>	 <p>QR code</p> <p>Type: H65G-VFXT22MF-B S/N: 000000-00000 24V DC, 27W, SELV, LIM Max. Surrounding Air Temp. :-20°C to 60°C Temperature Code: T4A MADE IN JAPAN</p> <p>Ind. Cont. Eq. for Haz. Loc. Ind. Cont. Eq. (E102542) IDEC CORPORATION</p> <p>Class I Div.2 Groups A, B, C, D. Enclosure Type 1, Type 4X Indoor Use only, Type 12 and/or <u>Type 13</u>.</p> <p style="text-align: center;">Type 13</p>

注: 其他规格不变

更改日期:

19年6月后生产的产品将使用新规格 (按实际库存而定)

www.idec.com/china

爱德克电气贸易(上海)有限公司

上海市静安区共和路 209 号企业中心第二座 8 楼 电话 (021) 6135 1515, 传真 (021) 6135 6225